

PS-6215/6216 Datasheet



System Configuration	
Processor	Intel TGL Core i3 Intel TGL Core i5 Intel TGL Core i7
System Memory	DDR4 SO-DIMM x 2, max. 64 GB
Supported Storage	M.2 SSD [Support both SATAIII signal] x 1
Intel vPro Support	Yes, depends on CPU installed
TPM	TPM 2.0
OS support	Windows 10 IoT 64 bit Windows 11 IoT GAC
Display & Touch	
LCD	PS-6215: 15" TFT LCD with LED backlight PS-6216: 15.6" TFT LCD with LED backlight
Resolution	PS-6215: 1024 x 768 PS-6216: 1366 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
I/O & Expansion	
Serial Port	DB9 x 2 + RJ50 x 1, 5V/12V support on all COM ports
Standard USB Port	USB 3.0 x 6 (on I/O plate) + USB 2.0 x 1 (on the top)
LAN Port	10/100/1000 Mb x 1
Display Port	HDMI (2.0) x 1
CR Port	CR port x 1, control 2 x CR via optional Y-cable, support 24V CR
Audio	Internal 2W speaker x 1
Internal Expansion Slot	1 x M.2 2230 for Wi-Fi/BT
Dimension	
W x D x H in mm	PS-6215: 372 x 252.7 x 320



	PS:6216: 372 x 252 x 291.4
Environmental	
Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

- Please note that this specification is preliminary, and is subjected to change without notice