

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled



\*Product image may differ from actual product

## One device. Many possibilities.

Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.

### Poly signature audio

Get more out of your conference calls with technology that reduces background noise, ensuring every inflection is heard.

### One-touch join

All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button.

## Featuring Flexible connectivity

Connect to multiple SIP and UC-cloud services simultaneously, which is ideal for multiple virtual meeting platforms in one room.

### Audio clarity

Echo cancellation and reverb elimination ensures audio clarity for natural conversations in any size space.

### Poly portfolio compatible

Complement your Poly room video solution with a fast, simple control from Trio C60.

### Scalable

Microphone expansion via additional microphones or daisy-chaining.

### Wi-Fi calling

Limit cabling with Wi-Fi 2.4-5 GHz audio conference calling.

### Simple UI

Meeting initiation is easy with Outlook calendar integration and one-touch join.

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled



\*Product image may differ from actual product

## Specifications

### Display

**Aspect ratio:** 16:9  
**Native resolution:** 720 x 1280  
**Panel technology:** Color LCD  
**Display size (diagonal):** 12.7 cm (5")  
**Touch-enabled:** Gesture-based, multi-touch capable touchscreen

### Connectivity and communications

**Wireless range:** Up to 6.1 m  
**External I/O ports:**  
1 USB 2.0 Type-A (for USB battery charging)  
1 USB 2.0 Micro-B (for USB audio device)  
2 RJ-45 (10/100/1000BASE-TX Mbps)  
**Wireless Technology:**  
Bluetooth® 4.2; Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20); 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

### User interface features

**Languages:** Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

### Audio

**Audio features:**  
Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression  
Comfort noise generation  
DTMF tone generation (RFC 2833 and in-band)  
Low delay audio packet transmission  
Adaptive jitter buffers  
**Microphone type:** Three cardioid microphones  
**Frequency response (microphone):** 100 Hz to 22 kHz  
**Sensitivity (speaker):** 92 dB  
**Audio codecs:** G.711 (A-law and  $\mu$ -law); G.722; G.722.1; G.722.1C; G.729AB; G.719; Polycom® Siren™ 7; Siren™ 14; iLBC; OPUS

### Other features

**Special features:** Unicode UTF-8 character support

### Power supply

**Power features:** LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4)  
LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment<sup>1</sup>

### Certifications

**Certified collaboration software:** Zoom; Open SIP

### Environmental

**Certifications and compliances:** AS/NZS 60950-1; AS/NZS 62368-1-17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9.1; ETSI EN 300 330; ETSI EN 301 893 v1.7.1; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1  
**Operating humidity range:** 5 to 95%  
**Operating temperature range:** 0 to 40°C  
**Storage temperature range:** -20 to 70 °C  
**Energy star certified:** ENERGY STAR® certified

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled

## Specifications

### Management

#### Management software:

Poly Zero Touch Provisioning  
RealPresence Resource Manager (v. 10.1 or above) based provisioning  
Polycom Device Management Service for Enterprise (PDMS-E)  
Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management  
SDP

### Display features

On-screen virtual keyboard

### Security

#### Security management:

802.1X Authentication and EAPOL Media encryption via SRTP  
Digest authentication  
Encrypted configuration files  
HTTPS secure provisioning  
Password login  
Support for signed software executables  
Support for URL syntax with password  
Transport Layer Security (TLS)  
Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)  
FIPS 140-2 compliant cryptographic module

### Headset and handset compatibility

#### Headset and handset compatibility:

Bluetooth® headset compatibility

### Telephony and call handling features

#### Telephony and call handling features:

Bundled with Polycom UC Software: Corporate Directory  
Access using LDAP  
Call timer and call waiting  
Call transfer, hold, divert (forward), park, pickup  
Called, calling, connected party information  
Distinctive incoming call treatment/call waiting  
Do not disturb function  
Local configurable digit map/dial plan  
Local five-way audio conferencing  
Shared call/bridged line appearance  
Visual Conference Management  
Up to 3 lines (maximum one Skype for Business and Microsoft Teams)  
Daisy-chain up to four  
One-touch speed dial, redial and meeting join

### Network

#### Supported network protocols:

DHCP VLAN discovery  
LLDP-MED for VLAN discovery  
FTP/TFTP/HTTP/HTTPS server-based central provisioning  
Manual or dynamic host configuration protocol (DHCP) network setup  
QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP  
Time and date synchronization using SNTP  
Provisioning and call server redundancy support

#### VoIP features:

IETF SIP (RFC 3261 and companion RFCs)

### Weight and dimensions

**Product Primary Color:** Black

**Weight:** 950 g

**Product dimensions:** 38.3 x 7.5 x 33.2 cm

**Package weight:** 300 g

**Package dimensions:** 48.3 x 11.5 x 39.4 cm

**Master carton quantity:** 5

**Master carton dimension:** 24.5 x 44 x 29.5 cm

**Master carton weight:** 13.26 kg

**Cartons per layer:** 4

**Pallet (layers):** 3

**Cartons per pallet:** 12

**Products per layer:** 20

**Products per pallet:** 60

**Pallet weight:** 357 kg

**Pallet dimensions:** 101.6 x 121.9 x 149 cm

**UPC number:** 197497506464

**Product number:** 849B4AA

**Product name:** Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled

### Warranty

Poly standard one-year limited warranty

### Country of origin

**Country of origin:** Made in China or Mexico

### What is in the box

Setup sheet  
Console  
Network (LAN) cable-CAT-5E  
Cable wrap  
Tactile overlay for improved accessibility

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled

---

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

February 2025  
gr-en

